

CRS-200 Suggested Product Specification

Part 2 - Products

2.01 Manufacturer

- A. Acceptable Manufacturer: Protek Systems, Incorporated, 1250 Wallace Dr. Unit B, Delray Beach, FL 33444; Telephone: 800-598-2153, Fax: 561-395-4771, www.proteksystem.com
- B. Substitutions: Not permitted.
- C. Provide all crash rail and wall protection from a single source.

2.02 Stainless Steel Crash Rails

- A. CRS-200 Stainless Steel Crash Rail by Protek Systems, Inc.
 - 1. Material: 16ga type 304 #4 satin finish stainless steel cover and mounting brackets
 - 2. Profile: 1 1/2-inch depth x 5 1/2-inch height with center V-groove
 - 3. Finish: #4 satin finish
 - 4. Installation: Supplied in standard lengths and cut to fit in field by installers
 - 5. Custom lengths and profiles available. Other stainless steel grades and finishes also available.

2.03 Components

- A. ECS-200 Stainless Steel End Plates
 - 1. Material: 11ga type 304 #4 satin finish stainless steel
 - 2. Size: 1 9/16-inch x 5 5/8-inch
 - 3. Installation: Attaches to end plate brackets with fasteners through pre-drilled countersunk holes
- B. CRBSE-200 End Plate Bracket
 - 1. Material: 16ga type 304 #4 satin finish stainless steel
 - 2. Secures CRS-200 cover to wall
 - 3. To be used at crash rail end points. Wings allow for end plate attachment.
- C. CRBS-200 Standard Bracket
 - 1. Material: 16ga type 304 #4 satin finish stainless steel
 - 2. Secures CRS-200 cover to wall
 - 3. Spaced evenly not to exceed 32-inches on center
- D. SPL-200 Splice Bracket
 - 1. Material: 16ga type 304 #4 satin finish stainless steel
 - 2. Secures CRS-200 cover to wall
 - 3. To be used as a splice where CRS-200 covers meet

CRS-200 Suggested Product Specification

E. Attachment Options

1. Fasteners: Pre-drilled holes available. Fasteners by others.